



### Additive for Alfix C2 Epoxy

#### Product

Fine PE-fibre filler for thickening Alfix C2 Epoxy.

#### Colour

White

#### Use

Alfix Thixotropic agent is used as a thickener for Alfix C2 Epoxy in cases where special conditions apply, for example:

- Joints width larger than 6 mm
- Deep joints/layer thickness
- Sloping surface
- Temperature conditions
- Increases the load bearing capacity of the adhesive
- Increases the filling of the joint

#### Consumption

Alfix Thixotropic agent can be added in quantities from a minimum of 0 g to a maximum of 300 g per 6.0 kg of Alfix C2 Epoxy.

Experience suggests adding 30 g (1 sachet) of Thixotropic agent per 6.0 kg.

Alfix C2 Epoxy can be used in most conditions, but particularly challenging conditions can require the addition of extra Thixotropic agent.

This should be decided on the basis of the task at hand.

#### Packaging

Alfix Thixotropic agent is supplied in weighed portions of 30 g/sachet.

#### Instructions for use

Add to the C2 Epoxy paste while mixing.

#### References

Product info

Alfix C2 Epoxy

Theme info: Grouting with Alfix C2 Epoxy.

Product information and safety data sheets are published on our website. You can also access them by scanning the QR code on the product packaging or via the Alfix app, which is available from the App Store or Google Play.

For further information, please consult our Technical Services Dept.

For latest update of this product info, visit [www.alfix.com](http://www.alfix.com)

#### Technical data

Working temperature

+15°C - +25°C

Shelf life

36 months when stored in cool, dry conditions in

original, unopened packaging.