



SEPTEMBER 2011

New products from Alfix

Alfix welcomes autumn with no less than 3 new products which were all launched in August.

DuraPuds for facade insulation

The Alfix DuraPuds range was successfully launched at the end of 2010 – comprising DuraPuds 710 (adhesive and thin render) and DuraPuds 703 (coloured render). The range is now extended by DuraPuds 810 (flexible fibre render) which is ideal for facade insulation.

DuraPuds 810 is recommended as a base and reinforcing render on critical substrates requiring special solutions. 810 is perfect for bridging cracks thanks to its reliable adhesion and flexibility which reduce the risk of crack formation. 810 is used for rendering facade insulation followed by either a finishing render or another top coat. Read more.

Facelifted white tile adhesive

Our well-known white tile adhesive, Alfix Universalfix, was introduced as the very first Alfix product as early as 1963 and has since formed the backbone of an ever-expanding tile adhesive range. Universalfix has been on the market for 48 years and has been developed and optimised continuously. Alfix has saved one of the original products from 1963, which is now stored safely in a separate glass showcase as a reminder of our first beginnings.



Universalfix has been renamed 'Letfix Universal'. The new name also involves new packaging as well as significant optimisation of the product to make it more flexible, easier to work with and also less amounts are required to complete a job. Like Universalfix, the

new tile adhesive is white and available in light blue bags. Letfix Universal is designed for fixing ceramic tiles, glass mosaic, translucent marble tiles and for large-size tiles. The tile adhesive is also suited for mounting insulation plates.

We are convinced that Letfix Universal will be an absolutely worthy successor of Universalfix.

Read more about the product.

High-strength cement-based grout

With the introduction of Cerafill 18, Alfix now offers distributors and end-users a highstrength cement-based grout. As indicated by its name, the grout is characterised by its resistance.

The new grout is particularly suitable for grouting ceramic wall and floor tiles in places subject to high mechanical load (such as high-pressure cleaning) and impact from cleaning chemicals. Examples of these demanding environments are car wash installations, workshops and swimming pools. The cement-based Cerafill 18 resistant can often replace epoxy sealing compound which can be difficult to apply. Read more.



